

Expertise Applied | Answers Delivered

8755 W. Higgins Road Suite 500 Chicago, IL 60631

www.littelfuse.com

To: Littelfuse Sales, Sales Support & Customers Valued Customer

From: Littelfuse Product Management - Industrial Business Unit

Subject: LPHV Information Update

Document Number: LFPCN_PG0124

Date: 04/26/2021

With regards to the above reference, Littelfuse would like to inform you about changes on interrupting rating for LPHV

Holder series from 20 to 50 kA.

There are NOT changes to Product Fit, Form or Function.

Old Information on Holder	New Information on Holder	Information Update
Series No. LPHV 1000VDC, 30A, 20kA, 4W Manufacturer Certified IEC 60269-2, -4, -6 75°C or 90°C CU Wire Dnly Wire Range: #8-14 Stranded #10-14 Solid Torque to 2 N-m (17, 7 IN. LBS.) DD NDIT DPEN WNDER LDAD Made in China	Series No. LPHV 1000/DC, 30A, 50kA, 4W Littelfuse Certified IEC 60/269-2, -4, -6 75°C or 90°C CU Wire Only Wire Range: #8-14 Standed #10-14 Solid Torque to 2 N-m (1.7. Tin. LBs.) DO NOT OPEN UNDER LOAD Made in China	Interrupting rating from 20 to 50 kA

Going forward / Timeframe

The effective date of this change was April 29 th, 2020.

These changes comply and within IEC/UL PV Fuse standard specifications.

I will appreciate if you could also send this e-mail to anyone else whom I could have un-intentionally missed out. Thank you for your continued business. If you have any questions, or need additional information please contact our Littelfuse representative.

Sincerely, Augusto Sánchez

Product Manager Industrial Business Unit

Littelfuse. Inc.

Office: +52 878-784-4734 Techline: +1 800-TEC-FUSE www.littelfuse.com/electrical