

Bill of Materials Change Description

MATERIALS	FROM	TO	REMARK
Die Attach	Able8290	Able8290	Same
Wire type	Gold Wire	Gold Wire	Same
Mold Compound	Sumitomo G770	Sumitomo G700	Changed
Lead Finish	Matte Sn	Matte Sn	Same

LFCSP 3x3 to 5x5mm

Package Outline Drawing(POD) Change Description

Body Size (mm)	Lead Count	Sawn LFCSP STATSChipPAC-China (SCC)				Sawn Type LFCSP ASE-Korea (AEK)			
		POD Spec	E-Pad Size (mm SQ.)	Lead Length (mm)	Lead Width (mm)	POD Spec	E-Pad Size (mm SQ.)	Lead Length (mm)	Lead Width (mm)
3X3	8	CP-8-13	1.74x1.45± 0.10	0.40 ± 0.10	0.25± 0.05	CP-8-11	2.34X1.60± 0.10	0.40 ± 0.10	0.25± 0.05
3X3	16	CP-16-27	1.50x1.50+0.15/-0.05	0.40 ± 0.10	0.25± 0.05	CP-16-22	1.60X1.60± 0.15	0.40 ± 0.10	0.23 +0.07/-0.05
4X4	16	CP-16-26	2.50x2.50± 0.10	0.40 ± 0.10	0.30± 0.05	CP-16-17	2.60X2.60± 0.10	0.40 ± 0.05	0.30± 0.05
4X4	20	CP-20-10	2.50x2.50± 0.15	0.40 ± 0.10	0.25± 0.05	CP-20-8	2.60X2.60+0.15/-0.25	0.40 ± 0.10	0.25 +0.05/-0.07
4X4	24	CP-24-7	2.50x2.50+0.15/-0.05	0.40 ± 0.10	0.25+0.05/-0.07	CP-24-14	2.34x2.34± 0.10	0.40 ± 0.10	0.23+0.07/-0.05
5X5	32	CP-32-11	3.50x3.50+0.15/-0.05	0.40 ± 0.10	0.25 +0.05/-0.07	CP-32-12	3.60X3.60+0.15/-0.05	0.40 ± 0.10	0.25+0.05/-0.07

Assembly Transfer of Select LFCSP Products to ASE Korea.

**LFCSP Package at ASE Korea
Qualification Results Summary**

QUALIFICATION RESULT			
TEST	SPECIFICATION	SAMPLE SIZE	RESULT
Temperature Cycle (TC)*	JEDEC <i>JESD22-A104</i>	3 x 77	PASS
Highly Accelerated Stress Test (HAST)*	JEDEC <i>JESD22-A110</i>	3 x 77	PASS
Autoclave (AC)*	JEDEC <i>JESD22-A102</i>	3 x 77	PASS
Solder Heat Resistance (SHR)*	JEDEC/IPC <i>J-STD-020</i>	3 x 11	PASS
High Temperature Storage (HTS)	JEDEC <i>JESD22-A103</i>	3 x 77	PASS

*Preconditioned per JEDEC/IPC J-STD-020